

Section 1 Identification

Trade Name: Velour and Leather Cleaner

Product Identification: 4670

Synonyms: Water-based alkali detergent

Product Use Description:

Automotive detail

General Info Phone: (800) 795-9222 Emergency Phone: (800) 535-5053

Supplier:

ABC COMPOUNDING CO. INC.

6970 JONESBORO RD Morrow, GA 30260

Section 2 Hazards Identification

Classifications

Skin corrosion - Category 1

Eye Damage - Category 1

Corrosive to Metals

Gasses under pressure - Liquefied gas



Compressed Gas

Corrosion

Signal Word: Danger

Hazard Statements

Keep out of reach of children.

Read label and SDS before use.

Causes severe skin burns and eye damage

Contains gas under pressure; may explode if heated.

May be corrosive to metals

Precautionary Statements

Prevention

Do not breathe mists.

Wash hands thoroughly after handling.

Wear protective gloves and clothing.

Wear eye and face protection.

Keep away from heat, sparks, open flames and hot surfaces. □ -No smoking.

Pressurized container: Do not pierce or burn, even after use.

Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with soap and water/shower.

Wash contaminated clothing before reuse.

If skin irritation persists, get medical attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center or a physician.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Immediately call a poison center or a physician

Absorb spillage to prevent material damage.

Trade Name: Velour and Leather Cleaner SDS #: 4670 Page 1 of 6
SDS ID: SDS00461 4670 Revision # 1 Revision Date 05/14/2015



Storage

Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 $^{\circ}$ C/ 122 $^{\circ}$ F. Store locked up.

Disposal

Dispose of contents and container in accordance with all local, regional, and national regulations.

Hazards Not Otherwise Specified

Not applicable

Section 3 Composition

		<u>Concentration</u>
Chemical Name	CAS#	% by Weight
Butane	106-97-8	>=1 <= 5
2-butoxyethanol	111-76-2	>=1 <= 5
Propane	74-98-6	>=1 <= 5
Trisodium Phosphate	7601-54-9	>=1 <= 5

Section 4 First Aid

EMERGENCY OVERVIEW

DANGER. May be harmful if swallowed. Causes severe skin burns and eye damage.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call a poison center or a physician.

SKIN: Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of soap and water/shower. If skin irritation persists get medical attention.

INHALATION: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or a doctor.

INGESTION: Rinse mouth. Do not induce vomiting. Seek medical attention immediately.

Section 5 Fire Fighting Measures



Suitable fire extinguishing media:

Use water spray, fog or foam.

Specific hazards arising from the chemical:

In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous thermal decomposition products:

Carbon Dioxide, Carbon Monoxide

Specific fire-fighting methods:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire fighters:

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

Section 6 Accidental Release Measures

Personal precautions:

Put on appropriate personal protective equipment (see section 8)

Environmental precautions and clean-up methods:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

Section 7 Handling and Storage

Do not use or store near heat, sparks or open flame. Exposure to temperatures above 120 F may cause bursting. Do not puncture or incinerate container. Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

Section 8 Exposure Controls/Personal Protection

2-butoxyethanol

ACGIH TLV 20 ppm OSHA PEL 25 ppm (skin)

Butane

ACGIH TLV 1000 ppm

Propane

ACGIH TLV 1000 ppm

Trade Name: Velour and Leather Cleaner SDS #: 4670 Page 3 of 6 SDS ID: SDS00461 4670 Revision # 1 Revision Date 05/14/2015



Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

Respiratory Protection: When respiratory protection is required use an organic vapor cartridge. A respiratory program that

meets OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements must be followed.

Engineering Controls: Good general ventilation required.

Section 9 Physical and Chemical Properties

Property <u>Value</u> **CLEAR SPRAY Appearance** Auto Ignition Temp **NOT AVAILABLE Boiling Point NOT AVAILABLE** Color **COLORLESS Decomposition Temperature NOT AVAILABLE Evaporation Rate NOT AVAILABLE Explosive Properties NOT AVAILABLE Explosive Limit Ranges** NOT AVAILABLE Flash Point NONE (liquid portion) Melting/Freezing Point **NOT AVAILABLE** Odor **MINT** Odor Threshold **NOT AVAILABLE** Other Information **NOT AVAILABLE** VOC content (wt. %): 6 Oxidizing Properties Physical State Partition Coeff NOT AVAILABLE LIQUID Relative Density Solubility (Water) **COMPLETE** 1.0 **NOT AVAILABLE** Vapor Density Vapor Pressure **NOT AVAILABLE**

Viscosity NOT AVAILABLE pH 12-13

Section 10 Stability and Reactivity

Reactivity: Under normal conditions of storage and use, hazardous reactions will not occur.

Chemical Stability: Stable under normal conditions.

Incompatible Materials: Acids and strong oxidizers

Conditions to Avoid : High temperatures, open flames, sparks, welding.

Decomposition Products: CO, CO2

Section 11 Toxicological Information

Primary Route of Entry: Skin contact, eye contact, inhalation

Acute/Potential Health Effects:

EYES: Causes severe irritation experienced as discomfort or pain, excess blinking and tear production, with redness and swelling of the conjunctiva.

SKIN: Brief contact may cause slight irritation. Prolonged contact may cause more severe irritation with pain, local redness and swelling and possible tissue destruction.

INHALATION: High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract.

INGESTION: May be harmful or fatal if swallowed. Corrosive. Can cause severe burns and complete tissue perforation of mucous membranes, mouth, throat and stomach.

Target Organ Effects: Liver, kidney, lungs and upper respiratory tract, gastrointestinal tract, eyes.

Reproductive/Developmental Information: 2-Butoxyethanol has caused red blood cell hemolysis in lab animals and secondary

injury to the liver and kidney.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

Acute Toxicity Values:

2-butoxyethanol: Ingestion - LD50, rat, 1300 mg/Kg; Dermal LD50, guinea pig 1400 mg/Kg; Inhalation - LC50, 1 hr, vapor, guinea pig > 3.1 mg/l

 Trade Name:
 Velour and Leather Cleaner
 SDS #:
 4670
 Page 4 of 6

 SDS ID:
 SDS00461 4670
 Revision # 1
 Revision Date 05/14/2015



Section 12 Ecological Information

2-butoxyethanol: EC50, Daphnia magna, static test, 48 h, immobilization: 1550 mg/l Bluegill sunfish, static test, 96 h, 1300 mg/l.

Section 13 Disposal Considerations

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

Section 14 Transport Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN number 1950

Proper shipping name Aerosols, nonflammable

Class 2.2

Packing group -

Section 15 Regulatory Information

Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (40 CFR 372.65) 2-butoxyethanol

If identified components of this product are **CERCLA** hazardous substances and/or listed under <u>Sections 302, 304, or 313 of</u>

<u>Title III</u> of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning and Community Right-To-Know Act), or under <u>California Proposition 65</u> (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic () Fire () Pressure (X) Reactive () Not Applicable ()

<u>T.S.C.A. Status:</u> All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

RCRA Status: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s)

D002

Section 16 Other Information

HMIS Ratings:

Trade Name:Velour and Leather CleanerSDS #:4670Page 5 of 6SDS ID:SDS00461 4670Revision # 1Revision Date 05/14/2015





Disclaimer: This Manufacturer believes that the information contained in the Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

Preparation/Revision Date: 5/14/15

 Trade Name:
 Velour and Leather Cleaner
 SDS #:
 4670
 Page 6 of 6

 SDS ID:
 SDS00461
 4670
 Revision # 1
 Revision Date
 05/14/2015