

## Section 1 Identification

**Trade Name:** Tire Bright Product Identification: 6429

Synonyms: Blend of Petroleum Distillates

Product Use Description:

Automative detail

General Info Phone: (800) 795-9222 Emergency Phone: (800) 535-5053

Supplier:

ABC COMPOUNDING CO. INC.

6970 JONESBORO RD Morrow, GA 30260

## Section 2 Hazards Identification

#### Classifications

Flammable liquids - Category 2 Aspiration Hazard - Category 1

Acute Toxicity - Inhalation - Category 4

Eye Irritation - Category 2 Skin Irritation - Category 2





Irritant

Flammable

Health Hazard

Signal Word: Danger

### Hazard Statements

Keep out of reach of children.

Read label and SDS before use.

Highly flammable liquid and vapour

May be fatal if swallowed and enters airways.

Harmful if inhaled

Causes skin irritation

Causes serious eye irritation.

#### **Precautionary Statements**

#### Prevention

Avoid breathing mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wash hands and face thoroughly after handling.

Wear protective gloves.

Wear eye protection.

Do not eat, drink or smoke when using this product.

Keep away from heat, sparks, open flames and hot surfaces. □ -No smoking.

Keep container tightly closed. Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/handling/ process equipment.

Use only non-sparking tools. Take precautionary measures against static discharge.

#### Response

IF SWALLOWED: Immediately call a poison center or a doctor. Do NOT induce vomiting.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical attention.

 Trade Name:
 Tire Bright
 SDS #:
 6429
 Page 1 of 6

 SDS ID:
 SDS00044
 6429
 Revision # 1
 Revision Date
 04/13/2015



Take off immediately all contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center or doctor if you feel unwell.

IN CASE OF FIRE: Use carbon dioxide, foam or dry chemical to extinguish.

#### Storage

Store in a well-ventilated place.

Keep cool.

Store locked up.

#### **Hazards Not Otherwise Specified**

Not applicable

#### Section 3 Composition

		Concentration
<u>Chemical Name</u>	<u>CAS #</u>	% by Weight
Light Hydrotreated Petroleum Distillate	68410-97-9	>=70 <= 80
Isopropanol	67-63-0	>=5 <= 10

## Section 4 First Aid

#### **EMERGENCY OVERVIEW**

DANGER. Flammable. May be harmful or fatal if swallowed. Aspiration hazard if swallowed. Vapor harmful. Keep away from heat and flame. Can cause nervous system depression.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs get medical attention. Take off contaminated clothing and wash it before reuse.

INHALATION: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

INGESTION: May be harmful or fatal if swallowed. Seek medical attention immediately. Do not induce vomiting.

## Section 5 Fire Fighting Measures

 Trade Name:
 Tire Bright
 SDS #:
 6429
 Page 2 of 6

 SDS ID:
 SDS00044
 6429
 Revision # 1
 Revision Date 04/13/2015



#### Suitable fire extinguishing media:

Use water spray, fog or foam.

#### Specific hazards arising from the chemical:

Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Runoff to sewer may create fire or explosion hazard.

#### Hazardous thermal decomposition products:

Carbon Dioxide, Carbon Monoxide

#### Specific fire-fighting methods:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

#### Special protective equipment for fire fighters:

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

## Section 6 Accidental Release Measures

#### Personal precautions:

Put on appropriate personal protective equipment (see section 8)

#### **Environmental precautions and clean-up methods:**

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

## Section 7 Handling and Storage

Do not get in eyes, on skin or on clothing. Avoid breathing sprays and vapors. Avoid skin contact. Keep out of reach of children.

Do not use or store near heat, sparks or open flame. Store in a cool, dry place. Ground/bond container and receiving equipment. Use explosion-proof ventilating and equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### Section 8 Exposure Controls/Personal Protection

Isopropanol

ACGIH TLV 400 ppm OSHA PEL 400 ppm

Light Hydrotreated Petroleum Distillate

ACGIH TLV 200 ppm

 Trade Name:
 Tire Bright
 SDS #:
 6429
 Page 3 of 6

 SDS ID:
 SDS00044
 6429
 Revision # 1
 Revision Date 04/13/2015



Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

Respiratory Protection: When respiratory protection is required use an organic vapor cartridge. A respiratory program that

meets OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements must be followed.

Engineering Controls: Good general ventilation required.

### Section 9 Physical and Chemical Properties

<u>Property</u> <u>Value</u>

Appearance CLEAR LIQUID Auto Ignition Temp NOT AVAILABLE

Boiling Point NOT AVAILABLE Color BLUE

Decomposition Temperature NOT AVAILABLE Evaporation Rate NOT AVAILABLE Explosive Limit Ranges NOT AVAILABLE Explosive Properties NOT AVAILABLE Flash Point 50 F Melting/Freezing Point NOT AVAILABLE

Odor SOLVENT Odor Threshold NOT AVAILABLE
Other Information VOC content (wt. %): 79 Oxidizing Properties NOT AVAILABLE

Partition Coeff NOT AVAILABLE Physical State LIQUID

Relative Density 0.8 Solubility (Water) INSOLUBLE Vapor Density NOT AVAILABLE Vapor Pressure NOT AVAILABLE

Viscosity NOT AVAILABLE pH NOT APPLICABLE

## Section 10 Stability and Reactivity

Reactivity: Under normal conditions of storage and use, hazardous reactions will not occur.

Chemical Stability: Stable under normal conditions.

Incompatible Materials: Acids and strong oxidizers

**Conditions to Avoid :** High temperatures, open flames, sparks, welding.

**Decomposition Products:** CO, CO2

Vapors may ignite at temperatures exceeding flash point.

### Section 11 Toxicological Information

Primary Route of Entry: Skin contact, inhalation, ingestion

#### Acute/Potential Health Effects:

EYES: May cause serious eye irritation. Symptoms include stinging, tearing and redness.

**SKIN:** May cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying of skin and skin burns.

**INHALATION:** High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage.

**INGESTION:** Harmful or fatal if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

Chronic / Long Term Effects: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Signs and Symptoms of Overexposure: Signs and symptoms of overexposure to this material through breathing, swallowing, and/or passage of material through the skin may include: stomach or intestinal upset (nausea vomiting, diarrhea) irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

 Trade Name:
 Tire Bright
 SDS #:
 6429
 Page 4 of 6

 SDS ID:
 SDS00044 6429
 Revision # 1
 Revision Date 04/13/2015



Target Organ Effects: Central nervous system.

Reproductive/Developmental Information:

WARNING: This product contains chemicals known to the State of California to cause birth defects or other reproductive harm.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

**Acute Toxicity Values:** 

Light Hydrotreated Petroleum Distillate: Inhalation - LC50, rat >7.63 mg/l; Oral - LD50, rat 5.17 g/Kg.

## Section 12 Ecological Information

Not available.

## Section 13 Disposal Considerations

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

### Section 14 Transport Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN number 1268

Proper shipping name Petroleum Distillates, n.o.s. (contains Petroleum Naphtha)

Class 3

Packing group ||

## Section 15 Regulatory Information

If identified components of this product are **CERCLA** hazardous substances and/or listed under **Sections 302, 304, or 313 of** 

<u>Title III</u> of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning and Community Right-To-Know Act), or under <u>California Proposition 65</u> (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic (X) Fire (X) Pressure () Reactive () Not Applicable ()

<u>T.S.C.A. Status:</u> All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

**RCRA Status:** Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s)

 Trade Name:
 Tire Bright
 SDS #:
 6429
 Page 5 of 6

 SDS ID:
 SDS00044
 6429
 Revision # 1
 Revision Date
 04/13/2015



D001

## Section 16 Other Information

## HMIS Ratings :



Disclaimer: This Manufacturer believes that the information contained in the Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

Preparation/Revision Date: 4/13/15

 Trade Name:
 Tire Bright
 SDS #:
 6429
 Page 6 of 6

 SDS ID:
 SDS00044
 6429
 Revision # 1
 Revision Date 04/13/2015