

Section 1 Identification

Trade Name: Eraser Product Identification: 6560

Synonyms: Water-based alkali detergent

Product Use Description:

Floor Finish Remover

General Info Phone: (800) 795-9222 Emergency Phone: (800) 535-5053

Supplier:

ABC COMPOUNDING CO. INC.

6970 JONESBORO RD Morrow, GA 30260

Section 2 Hazards Identification

Classifications

Skin corrosion - Category 1 Eye Damage - Category 1

Acute Toxicity - Oral - Category 4

Specific Target Organ Toxicity (single exposure) - Category 3

Corrosive to Metals



Signal Word: Danger

Hazard Statements

Keep out of reach of children.

Read label and SDS before use.

Causes severe skin burns and eye damage

May cause respiratory irritation.

Harmful if swallowed

May be corrosive to metals

Precautionary Statements

Prevention

Wash hands thoroughly after handling.

Wear protective gloves and clothing.

Wear eye and face protection.

Avoid breathing vapors. Use only in a well-ventilated area.

Do not eat, drink or smoke when using this product.

Keep only in original container.

Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with soap and water/shower.

Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center or a physician

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

 Trade Name:
 Eraser
 SDS #:
 6560
 Page 1 of 6

 SDS ID:
 SDS00314
 6560
 Revision # 1
 Revision Date
 05/08/2015



Immediately call a poison center or a physician. Absorb spillage to prevent material damage.

Storage

Store locked up.

Store in corrosive resistant plastic container.

Disposal

Dispose of contents and container in accordance with all local, regional, and national regulations.

Hazards Not Otherwise Specified

Not applicable

Section 3 Composition

		<u>Concentration</u>
Chemical Name	<u>CAS #</u>	% by Weight
2-butoxyethanol	111-76-2	>=5 <= 15
Potassium Hydroxide	1310-58-3	>=5 <= 15
Monoethanolamine	141-43-5	>=1 <= 5
Sodium Metasilicate	6834-92-0	>=1 <= 5

Section 4 First Aid

EMERGENCY OVERVIEW

DANGER. Harmful if swallowed. Causes severe skin burns and eye damage. May cause respiratory irritation.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call a poison center or a physician.

SKIN: Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of soap and water/shower. If

skin irritation persists get medical attention.

INHALATION: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or a doctor.

INGESTION: Rinse mouth. Do not induce vomiting. Seek medical attention immediately.

Section 5 Fire Fighting Measures



Suitable fire extinguishing media:

Use water spray, fog or foam.

Specific hazards arising from the chemical:

Containers may build pressure and rupture.

Hazardous thermal decomposition products:

Carbon Dioxide, Carbon Monoxide

Specific fire-fighting methods:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire fighters:

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

Section 6 Accidental Release Measures

Personal precautions:

Put on appropriate personal protective equipment (see section 8)

Environmental precautions and clean-up methods:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

Section 7 Handling and Storage

Do not use or store near heat, sparks or open flame. Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Avoid breathing fumes. Keep out of reach of children.

Section 8 Exposure Controls/Personal Protection

2-butoxyethanol

ACGIH TLV 20 ppm OSHA PEL 25 ppm (skin)

Monoethanolamine

ACGIH TLV 3 ppm OSHA PEL 3 ppm

Potassium Hydroxide

 ACGIH TLV
 2 mg/m3

 OSHA PEL
 2 mg/m3

Sodium Metasilicate

ACGIH TLV 10 mg/m3 OSHA PEL 15 mg/m3

 Trade Name:
 Eraser
 SDS #:
 6560
 Page 3 of 6

 SDS ID:
 SDS00314 6560
 Revision # 1
 Revision Date 05/08/2015



Eye Protection: Wear safety glasses or goggles.

Skin Protection: Wear impervious gloves (made from rubber, nitrile or neoprene), clothing, and boots.

Respiratory Protection: When respiratory protection is required, use an organic vapor & particulate cartridge. All respiratory

programs must meet OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements.

Engineering Controls: Good general ventilation required.

Section 9 Physical and Chemical Properties

<u>Property</u> <u>Value</u>

Appearance CLEAR LIQUID Auto Ignition Temp NOT AVAILABLE Boiling Point NOT AVAILABLE Color **COLORLESS Decomposition Temperature NOT AVAILABLE Evaporation Rate NOT AVAILABLE Explosive Limit Ranges NOT AVAILABLE Explosive Properties NOT AVAILABLE** Flash Point NONE Melting/Freezing Point **NOT AVAILABLE SASSAFRAS** Odor Threshold Odor **NOT AVAILABLE** Other Information VOC content (wt. %): 25 Oxidizing Properties **NOT AVAILABLE**

Partition Coeff NOT AVAILABLE

Relative Density 1.09 Solubility (Water) COMPLETE
Vapor Density NOT AVAILABLE Vapor Pressure NOT AVAILABLE

Physical State

LIQUID

Viscosity NOT AVAILABLE pH 12-13

Section 10 Stability and Reactivity

Reactivity: Under normal conditions of storage and use, hazardous reactions will not occur.

Chemical Stability:Stable under normal conditions.Incompatible Materials:Acids and strong oxidizers

Conditions to Avoid : High temperatures

Decomposition Products: CO, CO2

Section 11 Toxicological Information

Primary Route of Entry: Skin contact, eye contact, inhalation

Acute/Potential Health Effects:

EYES: Causes severe irritation experienced as discomfort or pain, excess blinking and tear production, with redness and swelling of the conjunctiva.

SKIN: Brief contact may cause slight irritation. Prolonged contact may cause more severe irritation with pain, local redness and swelling and possible tissue destruction.

INHALATION: High vapor concentrations may be irritating to respiratory tract.

INGESTION: Harmful or fatal if swallowed. Corrosive. Can cause severe burns and complete tissue perforation of mucous membranes, mouth, throat and stomach.

Chronic / Long Term Effects: None known.

Target Organ Effects: Liver, kidney, lungs and upper respiratory tract, gastrointestinal tract, eyes, skin.

Reproductive/Developmental Information: 2-Butoxyethanol has caused red blood cell hemolysis in lab animals and secondary

injury to the liver and kidney.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

Acute Toxicity Values:

 Trade Name:
 Eraser
 SDS #:
 6560
 Page 4 of 6

 SDS ID:
 SDS00314 6560
 Revision # 1
 Revision Date 05/08/2015



Monoethanolamine: Oral - LD50, rat 1720 mg/Kg; Dermal - LD50, rabbit 1025 mg/Kg

Potassium Hydroxide: Oral - LD50, rat 273 mg/Kg

2-butoxyethanol: Ingestion - LD50, rat, 1300 mg/Kg; Dermal LD50, guinea pig 1400 mg/Kg; Inhalation - LC50, 1 hr, vapor, guinea

pig > 3.1 mg/l

Section 12 Ecological Information

Potassium Hydroxide: Fish LC50, Western mosquitofish (Gambusia affinis), 80 mg/l, 96 hr. Monoethanolamine: Fish LC50, Pimephales promelas (fathead minnow), 227 mg/l, 96 hr. 2-butoxyethanol: EC50, Daphnia magna, static test, 48 h, immobilization: 1550 mg/l

Section 13 Disposal Considerations

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

Section 14 Transport Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN number 3266

Proper shipping name

Corrosive Liquid, Basic, Inorganic, n.o.s. (contains Potassium Hydroxide)

Class 8

Packing group ||

Section 15 Regulatory Information

CERCLA RQ (40 CFR 302)

Potassium Hydroxide

1000 lbs

Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (40 CFR 372.65) 2-butoxyethanol

If identified components of this product are **CERCLA** hazardous substances and/or listed under <u>Sections 302, 304, or 313 of</u> **Title III** of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning

and Community Right-To-Know Act), or under <u>California Proposition 65</u> (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

<u>Title III Section 311/312</u> Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic (X) Fire () Pressure () Reactive () Not Applicable ()

 Trade Name:
 Eraser
 SDS #:
 6560
 Page 5 of 6

 SDS ID:
 SDS00314 6560
 Revision # 1
 Revision Date 05/08/2015



<u>T.S.C.A. Status:</u> All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

<u>RCRA Status:</u> Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s)

D002

Section 16 Other Information

HMIS Ratings:



Disclaimer: This Manufacturer believes that the information contained in the Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

Preparation/Revision Date: 5/8/15

 Trade Name:
 Eraser
 SDS #:
 6560
 Page 6 of 6

 SDS ID:
 SDS00314 6560
 Revision # 1
 Revision Date 05/08/2015