AERO® brand aerosols are the finest available anywhere. A full range of solutions, from cleaning, to pest control. No other products can match our standards or our commitment to quality.

#### HIGHLIGHTS

- Non-flammable penetrating lubricant
- Displaces moisture
- Prevents corrosion

#### TYPICAL PROPERTIES

● Specific Gravity: 0.960

Propellant: Hydrocarbon

Spray Characteristics:Narrow Stream

Appearance: Clear yellow liquid

Odor: Solvent

● Net Weight: 20 ounces

• USDA: **H-2** 

#### SAFETY CAUTIONS

- Keep out of reach of children.
- Contents under pressure. Do not expose to heat or store at temperatures exceeding 120° F. Do not use near sparks or open flames. Do not puncture or incinerate container. Wrap empty container and put in trash collection.
- Refer to M.S.D.S. for additional safety information.

### HMIS RATINGS

Flammability



Reactivity

Personal Protection





# **Rust Free**

## Nonflammable 4 in 1 Oil

- Lubricates
- Prevents Corrosion
- Penetrates
- Displaces Moisture

Rust Free reduces hazards in the workplace by eliminating the extremely flammable characteristics of most penetrating sprays. It frees rusted and corroded nuts, bolts, studs, set screws, aluminum and copper fittings. Rust Free penetrates through grease, soil, and sludge. It lubricates and prevents corrosion on rusted and frozen parts. It is used in garages, factories, on farm machinery, marine and aeronautical equipment, in shops and homes.

#### **DIRECTIONS:**

- Hold container upright 6 to 8 inches from surface to be sprayed.
- Spray area to be treated liberally and allow sufficient time for complete penetration.
- Repeat treatment on extremely corroded parts.
- Tapping or heating may be required in some severe instances.

**DANGER:** Vapors harmful. Harmful or fatal if swallowed. Avoid breathing vapors. Avoid eye and skin contact. Use only with adequate ventilation.



NSF H2 Registered, meets USDA 1998 H2 Guidelines NSF Reg. No. 134661 Product Category: H2

distributed by:

