AERO® brand aerosols are the finest available anywhere. A full range of solutions, from cleaning, to pest control. No other products can match our standards or our commitment to quality.

#### HIGHLIGHTS

- Multi-purpose lubricant
- Open gear grease
- Extreme pressure applications
- High temperature (up to 550°F) applications

#### TYPICAL PROPERTIES

Specific Gravity: 0.780

● Solids: 50.0%

● Propellant: Hydrocarbon

Spray Characteristics:Harsh, circular, narrow spray

Appearance: Red, opaque liquid

Odor: Solvent

Net Weight: 14 ounces

● USDA: H-2

#### SAFETY CAUTIONS

- Keep out of reach of children.
- Contents under pressure. Do not spray while smoking or near heat, sparks or open flame. Do not puncture, incinerate, throw into fire, or store above 120° F.
- Refer to M.S.D.S. for additional safety information.

### HMIS RATINGS


Flammability



Reactivity

Personal Protection





# **Red Grease HD**

## Multi-purpose Bentone Based Lubricant Lubricates - Penetrates - Prevents Rust

This product is a heavy duty open gear grease designed for industrial use where a tacky, cohesive, high temperature and corrosion resistant grease is required. A non-melting grease for applications where extreme pressure and anti wear properties are a must; construction, fleet, marine, mining, steel and general industrial use.

- Resists corrosion, rust & oxidation.
- Non-melting with exceptional adhesives and cohesive properties.
- Will not squeeze out under severe shock load conditions.
- Withstands high temperatures.

#### **DIRECTIONS:**

- Shake well before using to insure proper mixing.
- Spray a thin film on the surface to be lubricated or protected.
- To apply to hard to reach areas, insert the extension tube provided into the valve cap.
- A thickened grease will form within seconds after application, and will be fully cured within minutes.

warning: Flammable! Avoid prolonged exposure to sunlight. Harmful if swallowed. If swallowed DO NOT INDUCE VOMITING. Vapor harmful. Use in well ventilated area. Avoid prolonged contact with skin. In case of contact with eyes, flush thoroughly with water. Deliberately concentrating the contents to breathe vapors may be harmful or fatal.



NSF H2 Registered, meets USDA 1998 H2 Guidelines NSF Reg. No. 134723 Product Category: H2

distributed by:

