

AERO® D'Limonene Degreasers are designed for a broad range of applications from light-duty institutional cleaning to heavy-duty industrial degreasing.



• Excellent for degreasing

HIGHLIGHTS

- Pleasant citrus fragrance
- Floating degreaser
- No petroleum distillates
- Slow evaporation

## TYPICAL PROPERTIES

- Specific Gravity: 0.81
- Dilution: Ready to use.
- Appearance: Green
- Odor: Citrus

SAFETY CAUTIONS

• Keep out of reach of children.


## • CAUTION: COMBUSTIBLE

• Make sure there is adequate ventilation.

• It is recommended that protective gloves and safety glasses be worn when using this product.

• Refer to M.S.D.S. for additional safety information.

HMIS RATINGS



## **Float** Floating Grease & Scum Solvent

**Float** consists of a blend of petroleum hydrocarbons and orange terpenes. It is a floating combination of solvents used primarily to dissove grease and scum that accumulates in grease traps, pumping stations, wet wells, and sewer lines.

DIRECTIONS-For Grease Traps: Start treatment immediately after the grease trap has been pumped. Add one quart per cubic foot of capacity, then begin preventive maintenance schedule one week later. Repeat procedure after pumping. For traps where scum blankets and grease cakes have already formed add one gallon per cubic foot directly to the grease trap. Repeat every 3 to 4 days until scum blanket is liquefied. **Preventive Maintenance:** One gallon daily per 40 cubic feet of trap capacity. For Pumping Stations, Wet Wells and Sewer Lines: Add 1% - 5% by volume (1-5 gallons per 100 gallons of capacity) as initial treatment. For preventive maintenance (daily application) use 0.25% (1 quart per 100 gallons of capacity). Solvent Cleaner: This product is excellent for removal of many printing inks, rosins ester gums, alkyd resins, tar and asphalt. Test on an inconspicuous area before using on painted

distributed by:

surfaces.



a division of: **ABC COMPOUNDING CO., INC.** Atlanta, Georgia Dallas, Texas