

aero® mold release

AERO® brand products are the finest available anywhere. No other products can match our standards or our commitment to quality.

HIGHLIGHTS

- Oil based silicone
- All purpose lubricant
- Mold release
- Odorless


TYPICAL PROPERTIES

- Specific Gravity: **0.78**
- Active Silicone: **15%**
- Appearance: **Clear**
- Odor: **Solvent**
- USDA: **H-2**

SAFETY CAUTIONS

- Keep out of reach of children.
- It is recommended that protective gloves and safety glasses be worn when using this product.
- Refer to M.S.D.S. for additional safety information.

HMIS RATINGS



Sil-Kote Release Agent

- all purpose lubricant ● mold release agent

SIL-KOTE eliminates sticking of foreign matter to metal surfaces such as snow plows, concrete trucks and various machinery.

This product works with all mold materials such as: Steel, Aluminum, Epoxy Resins, Rubber, Concrete and Elastomers. It has no corrosive or other harmful effect on the mold. A thin coating of this product does not alter dimensions or detail in the mold.

DIRECTIONS

Clean surface prior to application.

Use steel wool or wire brush and good detergent.

Wipe dry with clean cloth or allow to air dry.

Spray thin coat of undiluted product using trigger or pressure sprayer and holding 10 to 15 inches away from surface.

distributed by:

aero[®]
CHEMICAL COMPANY

a division of:
ABC COMPOUNDING CO., INC.
Atlanta, Georgia Dallas, Texas



NSF H2 Registered,
meets USDA 1998
H2 Guidelines
NSF Reg. No. 134658
Product Category: H2