AERO®'s Resilient Floor Care Line provides a product for every application and maintenance technique employed by today's floor maintenance supervisor.

HIGHLIGHTS

- Resilient tile sealer
- Penetrates and seals old porous tiles
- Extends life of floor finishes

TYPICAL PROPERTIES

● Specific Gravity: 1.01

• Solids: 12%

● pH: **8.5**

• Odor: Characteristic

Appearance: White Emulsion

SAFETY CAUTIONS

- Keep out of reach of children.
- It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation.
- Refer to M.S.D.S. for additional safety information.



Floor Tile Sealer Ready To Use Undercoat Sealer

This tough, durable product seals and prevents scuffing and marring on resilient floor surfaces. This product protects against traffic damage and extends the life of floor finishes. It is easily removable by non-ammoniated wax emulsifiers or ammoniated wax strippers.

DIRECTIONS:

- Strip floors thoroughly and prepare neutral dry floor.
- To seal, apply two thin coats, allowing at least 30 minutes drying time between coats.
- Daily maintenance requires sweeping and damp mopping or spray buffing.
- Heavy traffic lanes or worn areas should be recoated periodically.

HMIS RATINGS

Flammability



