

## **Ultra Bright** floor finish

ULTRA BRIGHT Floor Finish is based on the latest metal-free technology. It is a hard acrylic formulation, providing very high put-down gloss and good durability. It may be used with conventional low-speed or mop/recoat programs as well as with high speed burnishing equipment.

Advantages over conventional metal interlock finishes- GREAT REMOVABILITY, FASTER DRYING TIME, BETTER DURABILITY, NO AMMONIA ODOR and BETTER RE-COATABILITY

APPLICATION (New or Existing Floors): Thoroughly strip floor with PB FREE floor finish stripper. Rinse floor thoroughly with clean water. Apply a sealer base (optional) to worn floors or high traffic floors to improve wear-resistance and enhance gloss. Apply ULTRA BRIGHT in uniform thin coats allowing time to dry thoroughly between coats. If a sealer is used, apply up to four coats. If a sealer is not used, apply four coats for best results. Allow for longer drying time in damp weather.

MAINTENANCE: Sweep as necessary. Damp mop or scrub lightly with a mild, neutral detergent. Spray buff or buff lightly with appropriate pad. Also excellent for high-speed buffing. In high traffic areas, re-coat worn spots as necessary.

Safety Cautions: Keep out of reach of children. It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation. Refer to M.S.D.S. for additional safety information.

HMIS Ratings: Health: 1, Flammability: 0, Reactivity: 0, Maximum personal protection: B

## Typical properties:

1.02 Specific Gravity: 20% Solids: 7.5 pH: Leveling: Excellent Film formation: Excellent Gloss: Excellent Water resistance: Excellent Detergent resistance: Excellent Removability: Excellent Black heal mark resistance: Very good Appearance: White emulsion Odor: Mild acrylic

Available packaging: 4/1 gallon

2/2.5 gallon case 5 gallon pail

55 gal drum





Recognized for Safer Chemistry www.epa.gov/dfe



6554\_1201

