

HIGHLIGHTS Outstanding durability with low maintenance programs

Metal crosslinked all acrylic polymers

Superior dirt resistance

• Excellent burnish response with no powdering or dusting

• Decreased labor cost through less frequent need to buff, burnish and re-coat, and a reduction in the number of floor strippings

TYPICAL PROPERTIES

- Specific Gravity: 1.03
- Solids: 22%
- pH: 8.5
- James Static Coefficient of Friction: 0.6
- Leveling: Excellent
- Film Formation: Excellent
- Gloss: Excellent
- Water resistance: Excellent
- Detergent resistance: Excellent
- Removability: Excellent

 Black heal mark resistance: Excellent

- Odor: Mild acrylic
- Appearance: White emulsion

SAFETY CAUTIONS

Keep out of reach of children

• It is recommended that protective gloves and safety glasses be worn when using this product

• Make sure there is adequate ventilation

• Refer to M.S.D.S. for additional safety information

HMIS RATINGS Flammability Health 1 B Reactivity Personal Protection

Acrylic floor finish

- Extreme durability
- Superior dirt resistance

This metal-crosslinked, all acrylic floor finish provides superior durability and dirt resistance. It can be maintained with either conventional low-speed programs or infrequent (2-3 times a week) high speed burnishing.

to Believe!

USE DIRECTIONS (New/existing floors)

Thoroughly strip floor with a stripper. Rinse floor thoroughly with clean water. Apply a sealer base (optional) to worn floors or high traffic floors to improve wear resistance and enhance gloss. Apply 2-4 coats of floor finish in uniform thin coats allowing time to dry thoroughly between coats. Allow for longer drying time in damp weather.

MAINTENANCE: Sweep as necessary. Damp mop or scrub lightly with a mild, neutral detergent. Spray buff or buff lightly with appropriate pad. Also excellent for high speed buffing. In high traffic areas, re-coat worn spots as necessary.



Atlanta, Georgia / Dallas, Texas

Manufactured exclusively by: ABC Compounding Co., Inc. P. O. Box 16247, Atlanta, GA 30321 AERO is a registered trademark of ABC Compounding Co., Inc.