

aero[®] non-resilient floor care

AERO[®]'s Non-Resilient Floor Care Line provides a product for every application and maintenance technique employed by today's floor maintenance supervisor.

HIGHLIGHTS

- Quick acting seal and varnish remover
- Removes most: paints, varnishes, shellacs, polyurethanes, lacquers, etc.


TYPICAL PROPERTIES

- Specific Gravity: **0.928 ± .005**
- Emulsifiers: **2.0 ± 0.2%**
- Solvents: **93 ± 0.5%**
- Appearance: **Colorless liquid**
- Odor: **Solvent**

SAFETY CAUTIONS

- Keep out of reach of children.
- It is recommended that protective gloves and safety glasses be worn when using this product.
- Make sure there is adequate ventilation.
- Refer to M.S.D.S. for additional safety information and directions for use.

HIMIS RATINGS



Strip-Ease NMC

Paint & Resin Stripper

(Non-Methylene Chloride)

DESCRIPTION: A highly effective paint remover ideal for removing oil and latex based paints, shellacs, lacquers and polyurethanes from a variety of surfaces such as wood, metal, etc. Its slower evaporation rate prevents re-adhesion of coatings to surfaces. Unlike most non-methylene chloride paint strippers, it has a high flash point (over 100 deg. F) and does not contain such toxic chemicals as toluene, acetone, or MEK.

DIRECTIONS: Brush on surface and let soak for up to 30 minutes depending on the type and age of paint (two-part epoxy coatings may require soak times of 2 hours or greater).

distributed by:

aero[®]

CHEMICAL COMPANY

a division of:
ABC COMPOUNDING CO., INC.
Atlanta, Georgia Dallas, Texas