

aero[®] resilient floor care

AERO[®]'s Resilient Floor Care Line provides a product for every application and maintenance technique employed by today's floor maintenance supervisor.

HIGHLIGHTS

- High solids
- Excellent adhesion
- Extends life of floor finishes


TYPICAL PROPERTIES

- Specific Gravity: **1.02**
- Solids: **16%**
- pH: **9.0**
- Odor: **Slight ammonia**
- Appearance: **White emulsion**

SAFETY CAUTIONS

- Keep out of reach of children.
- It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation.
- Refer to M.S.D.S. for additional safety information.

HMIS RATINGS



Ultra Bond

Ready To Use Floor Sealer (for resilient flooring)

A high solids all acrylic sealer for resilient flooring such as vinyl, linoleum and asphalt tiles. Compatible with most water based floor finishes. Removable with conventional floor finish strippers.

Directions: Strip floors thoroughly and prepare neutral dry floor. To seal, apply one thin coat of ULTRA BOND and allow at least 30 minutes drying time. Then apply up to 4 coats of a floor polish of your choice, allowing at least 30 minutes drying time between coats. Daily maintenance requires sweeping and damp mopping or spray-buffing. Heavy traffic lanes or worn areas should be recoated periodically.

distributed by:

aero[®]
CHEMICAL COMPANY

a division of:
ABC COMPOUNDING CO., INC.
Atlanta, Georgia Dallas, Texas